



The Sullair Interim Tier 4 High Pressure Portable Air Compressor

MODEL 900XHH/1150XH

900/1150 cfm at 500/350 psig

25.5/32.5 m³/min at 34.5/24 bar


SULLAIR[®]
an Accudyne company

Designed for Total Accessibility and Reliability

Gauges and a LCD graphic display on the controller indicate:

- Discharge pressure and temperature
- Ambient air temperature
- Separator restriction
- Aftercooler air temperature
- Engine speed
- Hours of operation
- Voltage
- Engine coolant temperature
- Engine coolant low-level shutdown
- Fuel level and usage rate
- Fuel pressure and temperature
- Percent engine load
- Engine air temperature
- Engine oil pressure
- Engine exhaust module soot level
- Engine boost pressure
- Compressor and engine status

Additional Controller Features

- Engine diagnostic service port
- Diagnostic messages displayed on LCD screen
- Retrievable shutdown history includes all monitored system parameters at time of shutdown

- Back lit switches and gauges for night use
- E-stop, and auto and remote start capability
- Indicator lights for:
 - Low fuel
 - High compressor temperature
 - Compressor shutdown and warning
 - Engine shutdown and warning
 - Low fuel shutdown

0 to 100% Capacity Control

- Automatic inlet valve and unloaded starting

Complete Fluid Containment

- Heavy duty frame with complete fluid containment
- Bulkhead drain valves for all fluids are provided

Improved Serviceability

- Double doors on both sides of the compressor
- Serviceable components within easy reach

Two-Stage Dry Type Air Filters

- Filters incorporate safety elements and are positioned to draw cool ambient air

Two Mounting Options

- Highway towable tandem-axle (with Torflex® axles) includes electric brakes, oil bath wheel bearings, wheel chocks, restraining tow chains
- Less running gear on mounting rails with fork pockets

Low Emissions Engine Technology

- Complies with interim Tier 4 emissions legislation

Air End Warranty

- 5-year or 10,000-hour warranty when continuously serviced at the recommended intervals with Sullair HPL 1500 Compressor Fluid and filters

Quiet Operation

- Meets US EPA sound requirements of 76 dBA@7 meters

Dual Performance Available

- Two distinct compressor models available in one package

Additional Features

- No stacked coolers - allows for easy cleaning
- Cooler access panels

- Cold box design
- Fuel cooler is standard
- Single point lift
- Cabin lights
- (4) Heavy duty frame tie-downs
- Dedicated d-ring for service hose safety lanyard
- Controls at cold end of package
- Strobe light and siren provide visual and audible alerts for warning conditions
- Durable powder coat finish
- Galvanized canopy panels
- Remote fuel fill
- Stacked fuel valve for switching between internal and external tanks
- HPL 1500 compressor fluid

Customize the compressor to meet your specific requirement with Sullair options:

- Fork truck pockets
- Engine block heater
- Aftercooler
- Filtration for instrument quality air
- Spark arrestor muffler
- Aftercooler shutters
- Stainless steel canopy
- Air inlet shut-off valve
- Special paint

SULLAIR INTERIM TIER 4 900XHH/1150XHH HIGH PRESSURE PORTABLE AIR COMPRESSOR WEIGHTS AND DIMENSIONS

Designated Model	Weight (working)		Weight (dry)		Length (drawbar)		Length (canopy)		Width		Height		Track Width		Tire Size (load range)
	lbs	kg	lbs	kg	in	mm	in	mm	in	mm	in	mm	in	mm	
Tandem Axle (DTQ)	22200	10070	20600	9072	262	6655	210	5334	102	2591	101	2565	91	2311	245/70R17.5 (H)
Less Running Gear (DLQ)	21200	9616	19600	8890	-	-	210	5334	90	2286	86	2184	-	-	

ENGINE SPECIFICATIONS

Engine Make	Engine Type	Engine Model	Displacement		Cylinders	Bore and Stroke		Rated Speed	Rated Power	
			in ³	liter		in	mm	rpm	hp	kW
Caterpillar (Interim Tier 4 Emission Compliant)	Diesel	C15	928	15.2	6	5.40 x 6.7	137 x 170	1800	540 hp	403

MODEL AND RATING

Delivery @ Rated Pressure	Rated Pressure	Pressure Range
MODEL 900XHH/1150XH		
900/1150 acfm	500/350 psig	350-500 psig
425/542 l/s 25.5/32.5 m ³ /min	34.5/24 bar	24-34.5 bar

Capacity per CAGI/PNEUROP PN2CPTC3. (Annex D to ISO 1217)



Sullair
3700 East Michigan Boulevard
Michigan City, IN 46360
Telephone: 219-879-5451
www.sullair.com



Like us on Facebook.

© Copyright 2014 Sullair. All rights reserved.
The color green is a registered trademark of Sullair.
Specifications subject to change without notice.
SSL-1411EN 1404R

